

HIGHEST CLASS VISIBLE QUALITY

We are passionate about visual quality of our glulam. It is our mission to deliver visible quality glulam that meets and exceeds highest standards of aesthetics.

GET IN TOUCH

Jože Černivšek, s.p.
Juvanje 15
3333 Ljubno ob Savinji
Slovenija

+386 41 793 701
miha.cernivsek@siol.net

www.cernivsek.com

HISTORY

Three generations have been growing and modernizing the business. Originally it was a sawmill and in 1990 foundations of current modern facility have been laid. Today ČERNIVŠEK is specialized producer of BSH gluelam and solid structural timber KVH.

FLEXIBILITY AT THE CORE

We excel at delivering small orders of different dimensions and lengths.

EUROPE IS OUR HOME

We deliver to any part of Europe. We deliver larger orders with our own transport to enable really fast delivery when necessary.

TECHNOLOGY AND PEOPLE

We invest in technology as we believe robots are an essential part of high quality production. But it is still highly skilled employees that make the final touch and keep our customers satisfied. Our formula is: hi-tech and high-touch married.



GLULAM AND KVH SOLID TIMBER WOOD

QUICK AND FLEXIBLE

QUICK DELIVERY

Our business model enables us to respond very quickly to demands of our customers. Within two to three weeks we can supply complex orders of glulam of different sizes and lengths.

PRODUCTS

We are specialized in production of BSH glulam and KVH finger jointed kiln-dried solid timber wood. We offer CNC machining. All our products are certified.

BSH glulam beams / Standard dimensions (mm)

Width Height	80	100	120	140	160	180	200	220
80	•							
120	•	•	•					
160	•	•	•	•	•			
200	•	•	•	•	•	•		
240	•	•	•	•	•	•	•	•

Heights up to 600 mm with step of 40 mm possible in all above given widths.
Max. dimension of BSH glulam is 220x1300x18000 mm.

BSH glulam

Wood type: spruce or upon request
Length (max.): 18 m
Sizes (max.): 22x130 cm
Kiln-dried, wood moisture: 12% +-2%
Planed on four sides Packages packed in stretch film Melamin resin Suitable for use in service classes I and II
* I=Indoor climate, II=outdoor climate under roof

KVH Finger jointed structural timber wood

Wood type: spruce or upon request
Length (max.): 13,5 m
Sizes (max.): 10x24 cm
Kiln-dried, wood moisture: 12% +-2%



Glulam beams

Standard dimension of glulam beams (mm): 8x20, 10x20, 12x20, 16x20, 20x20, 24x24

Front door cornice

Upper layer	thickness 5 mm and 15 mm, free of knots/faults, D4 glue	72x145
Middle layer	56 and 32 mm, longitudinally laminated	42x145
Wood types	spruce, larch or upon request	
Lengths (m)	0,80 0,90 1,00 1,20 2,10 2,20	

Window Scantling / Windows scantling dimensions (mm)

DKD custom lengths	72x88	72x115	72x145	84x88	84x115	84x145
DKK custom lengths	72x88	72x115	72x145	84x88	84x115	84x145
KKK standard 6m length	72x78	84x88	/	/	84x115	84x145

Orders are practically custom made in dimensions and quantity. Standard wood is spruce or other types of wood upon request.